

INTERNATIONAL STANDARD

ISO
8849

First edition
1990-12-15

Small craft — Electrically operated bilge-pumps

Navires de plaisance — Pompes de cale à moteur électrique

STANDARDSISO.COM : Click to view the full PDF of ISO 8849:1990



Reference number
ISO 8849:1990(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 8849 was prepared by Technical Committee ISO/TC 188, *Small craft*.

STANDARDSISO.COM : Click to view the full PDF of ISO 8849:1990

© ISO 1990

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Small craft — Electrically operated bilge-pumps

1 Scope

This International Standard specifies requirements for electrically operated pumps intended for use in removing bilge-water from small craft. It applies to electrically operated bilge-pumps rated for less than 50 V direct current (d.c.).

2 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 8846:1990, *Small craft — Electrical devices — Protection against ignition of surrounding flammable gases*.

3 Definitions

For the purposes of this International Standard, the following definitions apply.

3.1 automatic pump: Pump that is equipped with a sensing means that activates and deactivates the pump at pre-determined liquid levels.

3.2 ignition-protected device: Device that complies with the requirements of ISO 8846. (See definition 2.2 in ISO 8846.)

3.3 nominal voltages: Voltages that are commonly used on small craft with direct current, such as 6 V, 12 V, 24 V and 32 V.

3.4 non-submersible pump: Pump designed to be operated above water.

3.5 submersible pump: Pump designed to be operated completely immersed in water.

4 General requirements

4.1 Bilge-pumps shall be designed to operate continuously at 120 % of nominal voltage at the point within the range of performance recommended for the pump that results in the highest power consumption.

4.2 Bilge-pumps and devices used to convert bilge-pumps to automatic operation shall be ignition-protected in accordance with the requirements of ISO 8846.

4.3 Bilge-pumps shall be rated in litres of water flow per minute or per hour at static pressures of both 0 kPa and 10 kPa. Bilge-pump capacities shall be determined at nominal voltage, measured at the pump.

4.4 Bilge-pumps shall be provided with means for securely fastening them to the boat.

4.5 Materials used in the construction of bilge-pumps which can be expected to come in contact with sea-water shall be

- selected or coated to be resistant to corrosion;
- galvanically compatible;
- resistant to deterioration by petrol (gasoline), oil and diesel fuel as well as bilge-cleaning agents.

4.6 Submersible pumps shall be provided with a strainer or other means of preventing debris entering the pump inlet. Inlet strainers and screens shall be designed such that they can be cleaned.