

Connector Accessories, Electrical, Strain Relief, 90°, Non-metallic, Category 4C
(For MIL-DTL-27599 Series I and MIL-DTL-38999 I and II Connectors)

This amendment forms a part of AS85049/46A Dated 2004-10

1). Present Requirement: (Sheet 1)

The complete requirements for procuring the accessories described herein shall consist of this specification sheet and the latest issue of SAE AS85049.

Change Requirements: (sheet 1)

NOTICE

The requirements for procuring the product described herein shall consist of this specification sheet and the latest issue of SAE AS85049.

Rationale for Change: Up-dated the procurement statement to comply with SAE guidelines.

2). Present Requirement: (Finish, sheet 3)

FINISH; NUT: A, W.

Change Requirement: (Finish, sheet 3)

Finish; Nut:

- A Black Anodized
- 1/ W Cadmium, Olive Drab
- X Nickel Fluorocarbon Polymer
- Y Pure Dense Electrodeposited Aluminum
- 1/ Z Zinc Nickel

1/ W and Z finish are not for use in space applications. Also see specification notes.

Rationale for Change: Added the X, Y and Z plating options and appropriate footnotes to this detail sheet in support of the AS85049B-A3 amendment.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2010 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://www.sae.org>

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/AS85049/46A_A1**